

Plastic bucket for adjustable floor box of 6 double elements for installation on pavement floor Simon Cima

REF. G66



BASIC INFORMATION

FINISH

Grey

MATERIAL

Various

COMPATIBILITY

With adjustable floor boxes of 6 double elements for pavement and inspection covers of 6 double elements Simon Series S.

ETIM CLASS

EC000114

TECHNICAL INFORMATION

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RECESS DIMENSION (MM)

259 x 312 mm

INSTALLATION AND MAINTENANCE

NUMBER OF CHANNEL ENTRIES

2

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

SCREWS REQUIRED FOR SLAB FIXING

Minimum 2 (1 on each side, diagonal). It is recommended to secure the mounting box with 4 screws for maximum secure fixation

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436016071

PRODUCT NET WEIGHT

1.438

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

6669680

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436016071

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.438

UNITARY PACKAGING VOLUME

6669680

PACKAGING HEIGHT

80

PACKAGING NET WEIGHT

1.438

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

263

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

1.438

PACKAGING LENGTH

317