

**Two-pole MCB 16 A for 3 elements with trim plate black
Simon K45**

REF. KF04A/14



BASIC INFORMATION

DESCRIPTION

With reference code KF04A / 14, we have this two-pole circuit breaker (16 Amps) of 3 elements and with trim plate. Its black finish makes it not only functional, but also in a product stylish. This is its version triple and has a module and half. This miniature circuit breaker is part of the Simon 27 collection, a series of Simon dedicated to the workplace solutions in the work stations. Before you buy it, please notice in its dimensions, which are 135 x 45 mm and, in terms of depth, 82 mm Also have present its, fixed to 6000 A. The trip Curve is the C. This miniature circuit breaker, it is suitable for installation in direct snap-fit trunking (wall), mini columns (floor), columns (ceiling), Ofiblocks and Teleblocks (furniture for office) of the series, K45, with 3 capacity mechanisms. On the other hand, it is not suitable for installation in wall-mounted boxes, floor boxes or the Simon K45 metal range of enclosures.

FINISH

Black

COMPATIBILITY

Columns, mini columns, Ofiblocks, Teleblocks and perimeter direct snap-fit trunking for Simon K45 mechanisms, with a minimum capacity for 3 K45 mechanisms.

PACKAGING CONTENTS

Two-pole MCB 16 A, trim plate and adaptor for Simon K45 housing

ETIM CLASS

EC000042

REMARKS

Not suitable for installation in wall boxes, floor boxes or the Simon K45 metal housing range.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

Up to 25 mm

AVAILABLE IN

Bipolar MCB, 10 A and 25 A differential with sensitivity of 30 mA

BREAKING CAPACITY (A)

6000 A

NUMBER OF CONNECTIONS PER TERMINAL

1 input per terminal connector

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

FORMAT

DIN

INDICATOR FUNCTION

No

CURRENT (A)

16 A

IP RATING

IP4X

KIT AVAILABILITY

No

LINKABLE

Yes, through busbars 68002-31

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 a 60° C

TYPE OF MECHANISM

Tilting

NUMBER OF MODULES

1 and a half modules

POWER SUPPLY (V~)

400 V~

RAL

7021

TRIP CURVE

C Curve

VERSION

Triple

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

10

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for installation in direct snap-fit trunking (wall), mini columns (floor), columns (ceiling), Ofiblocks and Teleblocks (furniture) from the K45 range with 3 capacity mechanisms

REMOVAL OF THE MCB

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

NUMBER OF TERMINALS

4 (2 terminal connectors per pole)

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60898-1:2003 + EN 60898-1:2003 A1:2004 + EN 60898-1:2003 A11:2005 + EN 60898-1:2003 A12:2008 + EN 60898-1:2003 A13:2012

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.285

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

2949750

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436042742

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

5

PACKAGING GROSS WEIGHT

1.665

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

95

PACKAGING NET WEIGHT

1.425

UNITARY PACKAGING GROSS WEIGHT

0.285

PACKAGING WIDTH

135

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

230