

2-way rotary dimmer switch 40 to 500 W/VA white Simon 32

REF. 32813-35



BASIC INFORMATION

DESCRIPTION

Control the light intensity of each room with the regulator 2-way switch rotary - of the collection Simon 32. With finishes in white and a simple design and modern, this mechanism Simon adapts to all kinds of decorative spaces and environments, adding maximum functionality and innovation. It is compatible with power supplies with a voltage of 230 Volts, supports an interval of intensity from 40 to 500 W / VA. It also supports a wire cross section of 1.5 to 2.5 mm and stripping of 5 mm The regulator 2-way switch Simon 32 -, you can reach a temperature range from 0 to 40 ° C and a maximum of -20 to the 75 °C. It has an installation with screw terminal connection that guarantees the integration of the set in the space, making its adapting to all types of ambientes.Sin, in the same circuit cannot be connected two electronic voltage regulators.

FINISH

White

COMPATIBLE WITH 230V INCANDESCENT AND HALOGEN LAMPS (W)

500 W/VA

COMPATIBLE WITH MECHANICAL SWITCH

No

COMPATIBILITY

Simon 32 frames with circular
central opening

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

PACKAGING CONTENTS

Dimmer and instruction sheet

COMPATIBLE WITH MECHANICAL 2-WAY/CROSSOVER SWITCH

Yes

ETIM CLASS

EC000025

REMARKS

Two main electronic voltage regulators cannot be connected in the same circuit.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	COMPATIBLE WITH FLUORESCENT LAMPS WITH 1- 10V DIMMABLE ELECTRONIC BALLAST	MAXIMUM QUANTITY PER CIRCUIT
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	No	1
NUMBER OF CONTACTS 3	COMPATIBLE WITH FLUORESCENT LAMPS (VA)	TYPE OF MECHANISM Rotary
NUMBER OF CONTROLLABLE CIRCUITS 1	No	MINIMUM POWER (W) 40
COMPATIBLE WITH HALOGENS WITH ELECTROMAGNETIC TRANSFORMER (W) 350 W	INDICATOR FUNCTION No	COMPATIBLE WITH MOTORS (VA) No
COMPATIBLE WITH ELECTRONIC AUXILIARY No	IP RATING IP20	OPERATING TEMPERATURE RANGE (°C) 0 - 40 °C
COMPATIBLE WITH HALOGENS WITH ELECTRONIC TRANSFORMER (W) No	COMPATIBLE WITH LOW CONSUMPTION (W) No	POWER SUPPLY (V~) 230 V~
	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	STORAGE TEMPERATURE RANGE (°C) -20 - 75 °C
	MAXIMUM POWER (W) 500	VERSION Single
NUMBER OF POSSIBLE ELEMENTS 1 element		NUMBER OF WIRES 2

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 5	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal and American	INSTALLATION TYPE Suitable for surface and flush mounting
--	--	---

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-2-1:2004 | EN 60669-2-1:2004 A1:2009 | EN 60669-2-1:2004 A12:2010 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.16

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

329232

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053012949

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

329232

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.16

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

57

PACKAGING NET WEIGHT

0.16

UNITARY PACKAGING GROSS

WEIGHT

0.16

PACKAGING WIDTH

76

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

76