

2-way switch for card with 2 micro switch and light indicator 250V~ graphite Simon 75

REF. 75550-38



BASIC INFORMATION

DESCRIPTION

This 2-way switch for card with 2 micro switches and indicator light (6 Amps - 250 Volt) in graphite finish and is part of the Simon 75 series, another successful collection of the brand. This success is due, without doubt, to all the possibilities it offers to level of functionality and design. In this case, this product is presented in individual version and has 1 single element. To be taken into account the following about the installation, and that is that we recommend that during the same is combined with a contactor / relay. When position, place the frame, it is important to break the flanges of the frame itself before manipulated by and install it. Also to take into account the stripping of wire: 0.5 millimetres. Its main feature is the signaling function (1mA consumption), however this 2-way switch provides the maximum level of security and protection to your electrical installation. If you have with other mechanisms Simon but of different series, do not forget to consult its compatibility.

FINISH

Graphite

COMPATIBILITY

Simon 75 frames

PACKAGING CONTENTS

Mechanism and cover

REMARKS

A contactor must be installed at the output of the mechanism. If this is not done, the maximum current of the switch is 10 A resistive (1.5 A inductive). It is recommended to protect the faston connectors with a heat shrink sleeve.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

Yes

NOMINAL VOLTAGE (V~)

250 V~

CABLE SECTION ADMITTED (MM)

0,5 mm

CURRENT (A)

10 (1,5 ind.) A

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CONSUMPTION INDICATOR (mA)

1 mA

IP RATING

IP20

POWER SUPPLY (V~)

250 V~

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

FREQUENCY

50 Hz

TYPE OF MECHANISM

Card

VERSION

Single

INSTALLATION AND MAINTENANCE

CLAW

Simon 27

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Faston

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for surface and flush
mounting

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 61058-1:2018 | EN 61058-1-1:2016 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.083

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

3017190

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053048634

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

1517738

UNITS CONTAINED PACKAGING

5

PACKAGING GROSS WEIGHT

0.415

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

82

PACKAGING NET WEIGHT

0.415

UNITARY PACKAGING GROSS
WEIGHT

0.083

PACKAGING WIDTH

83

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

223