

Corner accesory light module 4000K

REF. 86004300-184



BASIC INFORMATION

APPLICATION

Residential

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC002556

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

VOLTAGE (V~)

220/240 V~

LUMENS/W

117 lm/W

IP RATING

IP20

COLOR TEMPERATURE (K)

4000K

MACADAM STEPS

< 3 Step MacAdam

OPERATING TEMPERATURE RANGE (°C)

Ta Max 35°C

CONTROL

DALI

OPTICS

Opal

POWER SUPPLY (V~)

220/240 V~

CRI

80

POWER (W)

10.5 W

LUMENS (LM)

1230 lm

REGULATIONS

EAC MARKED

No

ECORRAE MARKED

No

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053299029

UNITARY PACKAGING HEIGHT

365

UNITARY PACKAGING WIDTH

50

UNITARY PACKAGING LENGTH

360

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

6570000

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.75

PRODUCT NET WEIGHT

0.6

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053299029

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

365

PACKAGING WIDTH

50

PACKAGING LENGTH

360

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

6570000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.75

PACKAGING NET WEIGHT

0.6

PACKAGING WEIGHT UNIT

KGM