

Adaptor plate for Simon 27 mechanical mechanisms for 1 element white Simon 500 Cima

REF. 50010088-030



BASIC INFORMATION

DESCRIPTION

Adaptative plate for Simon 27 mechanic mechanisms (in case of installing Simon 27 Play electronic mechanisms is necessary to use the reference 50011088-030), for 1 element, in white colour and belonging to the Simon 500 Cima series. With 1 module, and it is suitable for installation on the surface-mounted or by flush mounted, in places with a temperature located between the -5 to 60 ° C, although it can withstand extreme temperatures greater and is that it can withstand more than 60 ° C in the installation wall surface-mounted and more than 90 ° C in flush installation. Complies with the regulation European UNE -s 60670-1: 2006 and is made of halogen-free thermoplastic, this material is very safe as to prevent the propagation of the fire guarantees in case of fire and low toxicity in case of smoke. Its dimensions are 50 x 50 x 10,7 mm and to clean it, you will have to wipe it with a soft and dry cloth and never use or abrasive cleaners or cloths that contain chlorine in its formula.

FINISH

White

MATERIAL

Plastic

COMPATIBILITY

Simon 27 Play mechanical mechanisms

PACKAGING CONTENTS

Adaptor plate for Simon 27 mechanical mechanisms for 1 element

ETIM CLASS

EC002649

REMARKS

If installing Simon 27 Play electronic mechanisms, you will need to use article no. 50011088-030

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

NUMBER OF MODULES

1

AVAILABLE IN

Adaptor for Simon 27 Play mechanical mechanisms for 1 and 2 elements, with a specific version for Simon 27 Play electronic mechanisms for 1 element

KIT AVAILABILITY

No

RAL

9003

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

1 element

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C in surface-mount wall installation and +90 °C in flush-mount wall installation

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING

By direct snap-fit in the selected enclosure (no tools needed for fastening))

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface or flush-mount installation

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

UNE-EN 60.670-1:2006

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.007

PACKAGING LENGTH

140

UNITARY PACKAGING WIDTH

0

PRODUCT NET WEIGHT

0.007

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING
MEASUREMENT UNIT

MMT

PACKAGING EAN

8421053095690

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.07

PACKAGING WEIGHT UNIT

KGM

PACKAGING WIDTH

93

