


Custom button box 2 wait/enter functions for homes and offices white Simon 82 Sense

REF. 8000623-030



BASIC INFORMATION

FINISH

White

PACKAGING CONTENTS

Keypad and instructions

MATERIAL

Thermoplastic

ETIM CLASS

EC000205

REMARKS

Requires installation on LON or KNX bus coupling unit (8000100-039 or 8400100-039). Possibility of customising and creating your own configuration by choosing the functions you need from our icon library.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

NUMBER OF POSSIBLE ELEMENTS

1 element

INDICATOR FUNCTION

Yes

CURRENT (A)

6,2 mA

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Touch

OPERATING TEMPERATURE RANGE (°C)

0 - 45 °C

POWER SUPPLY (V~)

24 Vdc

RELATIVE HUMIDITY

From 20 to 85% (without condensation)

SLIDE CONTROL

No

SOUND FEEDBACK

Yes

STORAGE TEMPERATURE RANGE (°C)

25 - 70 °C

VIBRATION FEEDBACK

Yes

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-5:2016

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053128480

UNITARY PACKAGING HEIGHT

50

UNITARY PACKAGING WIDTH

76

UNITARY PACKAGING LENGTH

76

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

288800

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.033

PRODUCT NET WEIGHT

0.033

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053128480

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

273

PACKAGING WIDTH

74

PACKAGING LENGTH

84

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

129.688

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.033

PACKAGING WEIGHT UNIT

KGM