

## Downlight 725.25 WW Comfort High Flux

REF. 72525030-883



### BASIC INFORMATION

#### APPLICATION

Accent lighting, General lighting

#### PACKAGING CONTENTS

1 unit

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### IP RATING

IP44

### DRIVER INCLUDED

Yes

### LUMENS (LM)

3300 lm

### OPERATING TEMPERATURE RANGE (°C)

-10 - 35 °C

### L70 (°C)

30,000 h

### LUMENS/W

3300 lm/37W

### COLOR TEMPERATURE (K)

3000 K

### LIGHT BEAM APERTURE ANGLE (°)

120°

### OPTICS

General

### CONTROL

On/Off

### COLOR TYPE

WW

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### CRI

80

### LIGHTING EFFICIENCY (LM/W)

91,9 lm/W

### POWER (W)

37 W

### CHROMATICS CRI ICONS

CRI  
80

## INSTALLATION AND MAINTENANCE

### INSTALLATION ALTERNATIVES

Surface-mounted

### INSTALLATION TYPE

Flush-mounted

## REGULATIONS

### WARRANTY

3 years

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053089651

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

1.018

### PRODUCT NET WEIGHT

0.796

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053089651

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

117

### PACKAGING WIDTH

257

### PACKAGING LENGTH

257

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

7727733

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

1.018

### PACKAGING NET WEIGHT

0.796

### PACKAGING WEIGHT UNIT

KGM