Extension 0.5 metres for aluminium column with 1 side Simon 500 Cima

REF. **53555101-033**



BASIC INFORMATION

DESCRIPTION

If you are looking for maximum functionality and workplace solutions in the work area, the Simon 500 Cima range is a further step and offers the extension, 0.5 metres for pole of aluminium fixed to the ceiling. With 1 side and a dimension of 500 x 110 x 72 mm, it is suitable for installation on any floor type, whether raised or concrete floor, making the assembly to be carried out using telescopic guide attached to the ceiling slab., but if you want to ensure the robustness of the total structure, it is only possible to combine it with an extension of pole. Made in Anodised aluminium, it guarantees a greater resistance and durability of the product, providing, in addition, an innovative design and minimalist to make it work area owns the maximum security, functionality and design features of the collection Simon 500 Cima.

FINISH

Aluminium

MATERIAL

Aluminium

COMPATIBILITY

Simon 500 Cima, Simon 27 Play/Simon K45 (using adaptor) mechanisms and universal Simon mechanisms in combination with the universal box designed specifically for columns.

PACKAGING CONTENTS

Extension and installation manual

ETIM CLASS

EC000795

REMARKS

To ensure the robustness of the total structure, it is only possible to combine one extension per column

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

1 and 2 sides

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120 °C

EARTHING RESISTANCE

< 0.05 Ohms

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured with the metal divider guide supplied in the column.

IP RATING

IP4X

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to +120 °C

VERSION

1 side

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

TYPE OF FASTENING
Using connecting pins

INSTALLATION DIRECTION
Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE
Suitable for installing in any floor type, raised or concrete. Column secured by applying pressure to the ceiling slab using a telescopic guide.

REMOVAL OF TRIM FRAMES
Only with tool

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053101834

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.36

PRODUCT NET WEIGHT
1.36

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053101834

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
88

PACKAGING WIDTH
119

PACKAGING LENGTH
3040

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
31.835

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.36

PACKAGING WEIGHT UNIT
KGM