Accessory extensive ring 800.21

REF. **80091930-039**

BASIC INFORMATION

APPLICATION
General technical lighting

PACKAGING CONTENTS
1 Units

ETIM CLASS
EC002557

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP54

PHOTOBIOLOGICAL CLASSIFICATION
Categoría exento

SERVICE LIFE
50.000 h

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Recessed

REGULATIONS

WARRANTY
5 years 50.000 h

REGULATIONS
Dir. 2014/35/UE LVD |Dir. 2014/30/UE EMC|Dir. 2009/125/EC ErP (Reg. UE 2019/2020) |Dir. 2009/125/EC ErP (Reg. UE 2019/2015)|Dir. 2011/65/UE RoHS + post. mod|EN 60598-2-2:2012 |EN IEC 55015:2019 + A11:2020|EN 62493:2015 |EN 61547:2009|EN 62717:2017 + A2:2019 |EN IEC 61000-3-2:2019 + A1:2021|EN IEC 63000:2018 |EN 61000-3-3:2013 + A1:2019 + A2:2021

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053304631

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.18

PRODUCT NET WEIGHT
0.056

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053304631

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
5

PACKAGING WIDTH
150

PACKAGING LENGTH
150

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
112500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.18

PACKAGING NET WEIGHT
0.056

PACKAGING WEIGHT UNIT
KGM