

Flat voice and data plate with dust cover for 2 RJ45 Nexans® for 1 element aluminium Simon 500 Cima

REF. 50018089-033



BASIC INFORMATION

DESCRIPTION

Element of plate for Voice and data connections reference 50018089-033 belonging to the range professional components and products of the Simon 500 Cima series, suitable For different environments work and different systems for assembly. Plate in flat format of voice and data With dust cover for 2 RJ45 connectors with format for snap-fit Nexans ® of 1 element, Allows a maximum flexibility in connectivity for different presents systems. Aluminium in colours and finishes of the model, guarantees maximum security to Integrate metal components with self-extinguishing thermoplastic insulation Halogen-free, minimising the risk in situations of the flame or emission Gas. Ease of its fastening In vertical and horizontal enclosures without the need for an adaptor has a. Dimensions of 50 x 50 x 11 mm and a depth of 11 mm, being a piece Adaptable to different kinds of environments work and in different systems I installations professionals.

FINISH

Aluminium

PACKAGING CONTENTS

Flat voice and data plate with dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

Yes

NUMBER OF MODULES

1

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

Nexans® LANmark®-5 EVO, LANmark®-6 EVO.

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTORS

Not included in voice and data plate

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

RJ45 Nexans® connectors

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

RJ45 Nexans® connectors

DUST PROTECTION

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097076

PACKAGING VOLUME

0.604

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

54

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.028

PACKAGING WIDTH

52

PACKAGING NET WEIGHT

0.28

PRODUCT NET WEIGHT

0.028

PACKAGING LENGTH

215

PACKAGING WEIGHT UNIT

KGM

