

On-desk set with 6 German socket outlets aluminium Simon 400

REF. 42606000-133



BASIC INFORMATION

DESCRIPTION

Desk top kit complete finished in aluminium colour of the Simon series 400 and has 6 socket-outlets Schuko. It has dimensions of 295 x 120 x 80 mm and has a current of 16 A and a voltage of 250V. It is suitable to be flush mounted in furniture using clamps pages and to complete the installation of the product must be combined with the Simon 400 (references 4000XXX-03X). Its trim cover is made of painted steel, the lids fastenings in self-extinguishing thermoplastic and halogen-free (that promotes the no flame spread in case of fire and low toxicity level) and the profile is made in anodised aluminium. When cleaning this kit will only need to use a soft and dry cloth and forget you use abrasive cleaners or cloths containing chlorine, as it could be damaged and does not offer all its functions to full.

FINISH

Aluminium

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

NOMINAL VOLTAGE (V~)

250 V~

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

CURRENT (A)

16 A

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

IP RATING

IP30

RAL

9006

FORMAT

Schuko

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NUMBER OF SOCKETS

6 sockets for standard current circuit

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

VERSION

6 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

SECURING POSSIBILITIES

Using clips included in the fastening brackets

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

INSTALLATION TYPE

Suitable for fixing to furniture.

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053196199

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.15

PRODUCT NET WEIGHT

1.15

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053196199

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

330

PACKAGING WIDTH

125

PACKAGING LENGTH

95

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3918750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.15

PACKAGING WEIGHT UNIT

KGM