

Angled voice and data plate with dust cover for 1 element with 2 RJ45 category 6A FTP graphite Simon 500 Cima

REF. 50001086-038



BASIC INFORMATION

DESCRIPTION

Simon, always at the forefront of the highest technologies, offers in its Cima 500 range, plates that support Category 6A, FTP. This is cables for the transmission of data and analogue and digital signals, special for home automation installations. The cables are an advanced technology for transmitting data at high speed. Provide excellent features that exceed the requirements of the Cat 6 general, giving a performance way superior to existing cables on the market for this category. Simon guarantees through these systems, higher connectivity than the existing, and are designed for the future, their expansion and modularity depending on each need. This is a an angled voice and data plate with dust cover with 1 element and 2 RJ45 category 6A FTP, graphite finish Simon 500 Cima range, category 6A FTP. Compatible with RJ45 connectors of Keystone I, II, ATT ® / Avaya ®. Single Angled Plate. Plate for 1 and 2 RJ45. The plate includes clips for fastening in vertical and horizontal housings without the need for an adaptor. Dimensions 50 x 50 x 54 mm Supports Cabling 22-24 AWG. Metal components with self-extinguishing and halogen-free thermoplastic insulation that guarantees no flame propagation in case of fire and low toxicity in case of smoke resistant to corrosion and to changes in the temperature (-5 to 60 °C). Easy maintenance, clean with a soft, dry cloth is recommended not to use abrasive cleaners containing chlorine.

FINISH

Graphite

PACKAGING CONTENTS

Angled voice and data plate with dust cover, 2 RJ45 category 6A FTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

1

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Angled

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6A FTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097595

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.073

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.46

PRODUCT NET WEIGHT

0.073

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

