

Set of 2 push-button switches for blinds 10A 250V~ with fast terminal connection graphite Simon 24 Harmonie

REF. 2410331-038



BASIC INFORMATION

FINISH

Graphite

PACKAGING CONTENTS

Mechanism

COMPATIBILITY

Simon 24 Harmonie frames

ETIM CLASS

EC000044

TECHNICAL INFORMATION

AVAILABLE MARKET

CE, except for Spain, UK, Poland, Portugal, Andorra and Russia

CURRENT (A)

10 A

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

LATCH TYPE

For motors

VERSION

Double

IK CLASSIFICATION

01

TYPE OF MECHANISM

Rocker

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

14

INSTALLATION TYPE

Flush-mounted or surface-mounted

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

NM 06.6.001-2015

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053189122

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.069

PRODUCT NET WEIGHT

0.06

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053348154

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

92

PACKAGING WIDTH

91

PACKAGING LENGTH

336

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2812992

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.687

PACKAGING NET WEIGHT

0.6

PACKAGING WEIGHT UNIT

KGM