

## Spotlight 615 rail 4000 K Flood black

REF. 61500038-384



### BASIC INFORMATION

#### APPLICATION

Accent lighting

#### PACKAGING CONTENTS

1 unit

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CRI

80

### LIGHTING EFFICIENCY (LM/W)

100 lm/W

### IP RATING

IP20

### DIRECTIONAL

Yes

### LUMENS (LM)

2500 lm

### OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

### DRIVER INCLUDED

Yes

### LUMENS/W

2500lm/ 25W

### POWER SUPPLY (V~)

230 V~

### L70 (°C)

100,000 h at 25 °C

### OPTICS

Flood

### COLOR TEMPERATURE (K)

4000 K

### L90 (°C)

50,000 h at 25 °C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### CONTROL

On/Off

### COLOR TYPE

NW

### POWER (W)

25 W

### CHROMATICS CRI ICONS

CRI  
80

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

3-phase adjustable rail

## REGULATIONS

### WARRANTY

5 years

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053198698

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.846

### PRODUCT NET WEIGHT

0.635

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053198698

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

84

### PACKAGING WIDTH

177

### PACKAGING LENGTH

296

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

4400928

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.846

### PACKAGING NET WEIGHT

0.635

### PACKAGING WEIGHT UNIT

KGM