


Rocker with viewer for switch with pilot light for 1 element black Simon K45

REF. K112/14



BASIC INFORMATION

DESCRIPTION

With the rocker with viewer for 2-way switch in black finishes of the collection Simon 45, you will be able to know at all times the state of the load as indicates if, on which acts is on or off. It has a size of 45 x 45 mm and a depth of 10 mm, for half element, but also, you can find a version for 4. With an installation designed to be recessed or surface-mounted, the rocker with viewer Simon 45, is made up of halogen-free thermoplastic that prevent the flame spread and toxicity by smoke, in case of fire. You can forage temperatures of more than 60 °C. With a design adapted to the needs of each space, in black finishes and with signalling function and pilot light of the load, the rocker with viewer Simon 45 is perfect for a maximum functionality in its working area.

FINISH

Black

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Rocker and installation manual

ETIM CLASS

EC000011

REMARKS

Used to determine with the pilot light whether the load on which it acts is on or off

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

AVAILABLE IN

Quarter and half module versions

KIT AVAILABILITY

No

NUMBER OF MODULES

Half

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

7021

INDICATOR FUNCTION

Yes

VERSION

Single

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2:2008

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

PRODUCT NET WEIGHT
0.096

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING VOLUME
544320

UNITARY PACKAGING LENGTH
0

PACKAGING EAN
8426436047082

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
544320

UNITS CONTAINED PACKAGING
10

PACKAGING GROSS WEIGHT
0.96

UNITARY PACKAGING VOLUME
UNIT
MMQ

PACKAGING HEIGHT
72

PACKAGING NET WEIGHT
0.96

UNITARY PACKAGING GROSS
WEIGHT
0.096

PACKAGING WIDTH
72

PACKAGING WEIGHT UNIT
KGM

PACKAGING LENGTH
105