

Multisensor True Presence HF+LUX recessed box DALI-2 Input white IP20

REF. 89220324-230



BASIC INFORMATION

DESCRIPTION

Presence and luminosity multisensor for flush mounting. The recommended installation height is 2.8 m, with a maximum height of 12 m. It has a detection angle of 360° and an opening angle of 160°. The tangential detection range is 15 m and the radial detection range is 15 m.

The luminosity regulation range is 2 - 2000 lux. The detector configuration is performed via Bluetooth application and DALI.

It has a TEACH operating mode. Possibility of interconnection between sensors via Bluetooth. The control protocol is DALI-2 Input.

The power supply voltage is 220-240 VAC, with a typical DALI consumption of 2 mA. The operating temperature of the detector is: 0 - 50 °C.

White finish, IP 20 protection rating, and dimensions: 123 x 123 x 51 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI2 Slave

IP RATING

IP20

RAL

9003

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053383490

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.295

PRODUCT NET WEIGHT

0.18

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053383490

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.295

PACKAGING NET WEIGHT

0.18

PACKAGING WEIGHT UNIT

KGM