

Beacon Spot Way BT Mesh 8W with detector 10m PIR+LUX anthracite IP44 3Y

REF. 89397602-873



BASIC INFORMATION

DESCRIPTION

Beacon with PIR detector and Bluetooth connectivity. The power is 7.9 W, the luminous flux is 512 lm, and the color temperature is 3000 K. The maximum installation height is 4m, and the installation is on the floor. The detection range is 10 mm, and the detection angle is 90 °. The luminosity regulation range is 2 - 2000 lux, and the timing range is 5 s - 60 min. The configuration of the luminaire is done through a Bluetooth application. Possibility of interconnection between luminaires via Bluetooth mesh. The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C. Protection grade IP 44 and IK 03, and dimensions: 226 x 140 x 572 mm. 3-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Anthracite

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP44

IK CLASSIFICATION

03

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053400500

UNITARY PACKAGING GROSS WEIGHT

1.967

PACKAGING LENGTH

528

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

1.136

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053400500

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.967

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

180

PACKAGING NET WEIGHT

1.136

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

184

PACKAGING WEIGHT UNIT

KGM