

Wall movement and brightness detector 240° 12m white IP54 3Y

REF. 89101143-630



BASIC INFORMATION

DESCRIPTION

Wall-mounted PIR motion and brightness detector. The recommended installation height is 2 m, with a maximum height of 4 m. It has a detection angle of 240° and an opening angle of 180°. The tangential detection range is 12 m and the radial detection range is 5 m.

The brightness regulation range is 2 - 2000 lux and the timing range is 10 s - 15 min. The configuration of the detector is done through potentiometers.

The control output is On/Off and the maximum switchable power is 1000 W (350 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C.

White finish, IP 54 protection rating and dimensions: 60 x 90 x 100 mm.

3-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000133

COMPATIBILITY

Simon Sensor Pro

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

1000

RAL

9010

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

1.8

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053356531

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.305

PRODUCT NET WEIGHT

0.221

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053356531

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

90

PACKAGING LENGTH

135

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1944000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.305

PACKAGING NET WEIGHT

0.221

PACKAGING WEIGHT UNIT

KGM