

Adjustable floor box kit for concrete floor 6 elements with 2 double sockets and 2 plates for 1 RJ45 grey Simon 500 Cima

REF. 52006301-030



BASIC INFORMATION

DESCRIPTION

From the Simon 500 Cima series comes this with adjustable floor box kit for concrete floor and 6 elements with 2 double socket and 2 plates for 1 RJ45. In the format Schuko socket and snap-fit RJ45 Keystone I, II, ATT ® / Avaya ®. Finished in grey, with 2 double sockets for standard current circuits. When installing mounted, keep in mind that it has a click terminal connection (1 click ®). To complete a successful installation of this product, it must be combined with a plastic tray (reference 52052103-035), or if you prefer, with a metal tray (ref.52052203-033). Optionally, we recommend combining it with the flush-mount trim cover (reference 52053103-035) in cases where you do not install the same floor covering. This kit is specially designed and designed for assembly in concrete floor, although it is also suitable for installation in raised floor. Manufactured with different metal materials that have properties self-extinguishing and halogen-free. In case of fire, you will get the maximum protection.

FINISH

Grey

COMPATIBILITY

Simon 500 CIMA mechanisms

ETIM CLASS

EC000024

MATERIAL

Plastic

PACKAGING CONTENTS

Kit, metal partition wall, ground connection cable, screws and installation manual

REMARKS

To complete the installation of the product, it must be combined with a plastic tray (ref.52052103-035) or with a metal tray (ref.52052203-033). Alternatively, it may be combined with flush-mount trim cover (ref.52053103-035) in cases where the same floor lining is not installed.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam

NUMBER OF CLAMP-HOLDER HOLES

8

NUMBER OF CONNECTIONS PER TERMINAL

1 terminal connection for click terminal connection system and 2 terminal connections for the fast terminal connection system

COMPATIBLE WITH CONNECTORS

Simon®, AMP netconnect® Standard 110, SL110, SL Tool-less, 216000 and 216005, Brand-Rex®, ADC Krone® KM8 Keystone, BeldenCDT® Giga Flex Keystone, Ersys®, General Cable®, Molex®, Panduit® Netkey, Ortronics® Clarity TechChoice Keystone, Rit® and other manufacturers with Keystone snap-fit system.

NUMBER OF CONNECTORS

2

RJ45 CONNECTORS

Not included

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

DUST SHUTTER

Yes

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured by installing the metal partition wall in the housings fitted into the box for this purpose.

FORMAT

Schuko

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

IK CLASSIFICATION

08

INDICATOR FUNCTION

Yes

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

CURRENT (A)

16 A

IP RATING

IP4X

LED CONSUMPTION INDICATOR (MA)

0.55

LINKABLE

Yes, the sockets for a single circuit are supplied linked together.

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

1700kg

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

6 modules

NUMBER OF PLATES

2 voice and data plates

PLATE TYPE

Flat

RAL

7011

RECESS DIMENSION (MM)

170 x 210 mm

RJ45 ADAPTOR MODULE

Included in voice and data plates

NUMBER OF SIDE ENTRANCES

12

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

0

CLAW RANGE OF OPERATION (MM)

Between 14 and 54 mm

REMOVAL OF CONNECTOR

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Using fastening claws on the concrete tray (supplied with the floor box)

REMOVAL OF THE FRAME

Only with tool

CAN BE INSTALLED IN TRAY

Plástica y metálica

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Specially designed to be installed in concrete floors, although it is also suitable for installation in raised floors

REMOVAL OF THE PLATE

Only with tool

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

NUMBER OF TERMINALS

3 inputs and 3 outputs

REGULATIONS

REGULATIONS

UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053101384

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.54

PRODUCT NET WEIGHT

1.54

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053101384

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

75

PACKAGING WIDTH

200

PACKAGING LENGTH

230

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3.45

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.54

PACKAGING WEIGHT UNIT

KGM

