

Flat voice and data plate without dust cover for 1 element with 1 RJ45 category 6 UTP white Simon 500 Cima

REF. 50002185-030



BASIC INFORMATION

DESCRIPTION

This is a voice and data plate in flat format with dust shutter of 1 element for 1 RJ45 connector category 6 UTP. The article is white in colour, measures 50x50x32,5 mm and is part of the Simon 500 Cima series, a collection whose mechanisms have been designed to facilitate the workplace solutions in any environment. It is in compliance with the current regulation and consists of metal components with halogen-free in self-extinguishing halogen-free thermoplastic material, a 100% safe in case of fire, as it avoids the fire is propagate and guarantees the low toxicity in the presence of smoke. The product comes with clips for its proper fastening in vertical and horizontal enclosures. There is no need adapter. In terms of the cleaning of the plate, the manufacturer recommends using a soft and dry cloth and to avoid, as far as possible, abrasive cleaners containing chlorine.

FINISH

White

PACKAGING CONTENTS

Flat voice and data plate without dust cover, RJ45 connector category 6 UTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

No

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6 UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053098127

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.06

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.2

PRODUCT NET WEIGHT

0.06

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

