Double French socket 16 A 250V~ bicolor with safety device, light indicator and screw terminal connection red-white Simon Cima

REF. **S2/6/9**



BASIC INFORMATION

FINISH

White

COMPATIBILITY

With all the enclosures from the Simon Cima range.

ETIM CLASS

EC000125

TECHNICAL INFORMATION

FORMAT
French

HEAT RESISTANCE (°C)
+125 °C (in accordance with standard IEC 60695-10-2)

INDICATOR FUNCTION
Yes

CURRENT (A)
16 A

IP RATING
IP20

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MONOBLOCK
No

RAL
9003

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
12

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLATION DIRECTION
Horizontal, Vertical

REMOVAL OF THE SOCKET
Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436043985

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
3524976

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.112

PRODUCT NET WEIGHT
0.112

UNITARY PACKAGING WEIGHT UNIT
KGM

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
112

PACKAGING WIDTH
117

PACKAGING LENGTH
269

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3524976

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.12

PACKAGING NET WEIGHT
1.12

PACKAGING WEIGHT UNIT
KGM