

DALI downlight white 735.20 WW Extensive

REF. 73520330-783



BASIC INFORMATION

DESCRIPTION

Downlight 735.20 WW Extensive DALI Luminaire type downlight indoor, flush mounted. Optics EXTENSIVE. Light distribution only with LED. Design thought to a general lighting with high performance of comfort and brightness. Ideal for hospitals, hotels, etc. based on a reflector with high reflectance that directs the light downwards at an angle of 85 °, and with a diffuser that directs the light beam gently towards the exterior. To be flush mounted or surface-mounted position, place on the ceiling, using accessories. System DALI of conventional push-button switch, warm colour temperature (WW). Made in polycarbonate body and with aluminium heat sink. 1,300 kg power 24 W IP 20. 1-10 V CRI 80. 2300 lm. Finishes white and aluminium. 230 mm diameter 110 mm Luminaire Photobiological safety, this is that offers protection against the adverse effects potential of radiation in the optics on the skin and in your known as photobiological risks, resulting from the blue light of the spectrum.

APPLICATION

General technical lighting

PACKAGING CONTENTS

1 Unit

TECHNICAL INFORMATION

FREQUENCY

50 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

96 lm/W

IP RATING

IP20

ELECTRICAL CLASS

type 1

LUMENS (LM)

2300 lm

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

2300 lm/24W

POWER SUPPLY (V~)

220/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Extensive

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

50,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

DALI

LIGHT BEAM APERTURE ANGLE (°)

85°

POWER (W)

24 W

CRI

80


COLOR TYPE

WW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Ceiling surface mount

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

150

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053136478

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.5

PRODUCT NET WEIGHT

1.2

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053136478

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

135

PACKAGING WIDTH

285

PACKAGING LENGTH

255

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

9811125

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.5

PACKAGING NET WEIGHT

1.2

PACKAGING WEIGHT UNIT

KGM