

Customisable flush-mounted in the desk kit with dual opening cover and fins, 4 German socket outlets and 8 empty elements aluminium Simon 400

REF. 47602000-133



BASIC INFORMATION

DESCRIPTION

When counting with 8 empty elements, you can customize this kit within a desk, also has cover for 2 opening, fins and 4 SCHUKOS with an aluminium finish, this piece belongs to the series Simon 400, a series designed to offer a solution inclusive aesthetic wherever it is installed, as it has a manual elevation system. It has a dielectric strength with no holes or contours with 2000 V at 50H during 1 minute, a voltage of 250 V, a current of 16 A and a insulation resistance > 5 M? at 500 V. This kit stands out for its materials, the enclosure is painted steel, its profile of anodised aluminium and its covers and fastenings are manufactured in self-extinguishing halogen-free thermoplastic that we guarantees the no-propagation of the flame, and low toxicity in the event of fire and smoke.

FINISH

Aluminium

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with metal fin

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

NUMBER OF POSSIBLE ELEMENTS

8

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9006

NUMBER OF REAR ENTRANCES

8

RECESS DIMENSION (MM)

318 x 175 mm (± 2mm)

NUMBER OF SOCKETS

4 sockets for standard current circuit

VERSION

12 elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With metal fin

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

REMOVAL OF COMPONENTS

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure.

Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45° and 135°

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053197486

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053197486

PACKAGING VOLUME

9990000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

370

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

135

PACKAGING NET WEIGHT

3.5

UNITARY PACKAGING GROSS
WEIGHT

3.5

PACKAGING LENGTH

200

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

3.5