

Pull-cord push button 10A 250V~ with fast terminal connection system ivory Simon 31

REF. 31652-31



BASIC INFORMATION

DESCRIPTION

The series 31 of Simon stands out for the special control mechanisms included within the wide catalogue of this range. For example, customers can you in the handler Push-button switch with a current of 10A, a voltage of 250V~ and screw quick terminal connection system in ivory finish, some of its features are: Dimensions of 64x65 mm, wire section from 0.2 to 0.5 mm and wire stripping of 13 mm and pull-cord operation. The metal components with halogen-free thermoplastic insulation and thermoplastic trim with which it has been manufactured stand out for their durability and resistance to shocks and extreme temperature conditions. Also, it is available in 2 finishes, so it is recommended to choose a frame with the same colour as the rocker selected to achieve the most appropriate for each situation.

FINISH

Ivory

PACKAGING CONTENTS

Mechanism with rocker

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC000029

REMARKS

Available in 2 finishes. It is recommended to choose a frame the same colour as the selected rocker.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 AX

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Pull handler

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

13

INSTALLATION TYPE

Suitable for surface and flush mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 61058-1:2018 | EN 61058-2-1:2011 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
3409560

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.103

PRODUCT NET WEIGHT
0.103

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053007372

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
82

PACKAGING WIDTH
165

PACKAGING LENGTH
252

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
3409560

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.025

PACKAGING NET WEIGHT
1.03

PACKAGING WEIGHT UNIT
KGM