German socket outlet 16A 250V~ with safety device and fast terminal connection white Simon 27 Play

REF. **27432-65**



BASIC INFORMATION

DESCRIPTION

Quality at the best price. This is how we could define the Socket-outlet with lateral Schuko ground connection, with 16A current and 250V~ voltage and white fast-terminals connection of the Simon 27 Play series (45x45 mm) includes a safety device that makes it perfect for rooms with minors in which we want to avoid any type of unexpected accident, as the covers include the child protection function. It is ideal to assemble in new work or to replace in reforms carried out in certain rooms of a home or a company, its installation is carried out by means of insertion, making it the most popular choice for use in offices, hotels, health centres, educational centres or commercial establishments. The metal components with halogen-free thermoplastic insulation and thermo-stable trim with which it has been manufactured stand out for their durability and resistance to the adverse elements of the ambience in which it is located.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Socket outlet with cover

ETIM CLASS

EC000125

REMARKS

The covers include a child-proof protective feature.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
2,5 mm

NUMBER OF POSSIBLE ELEMENTS
1 element

FORMAT
Schuko

INDICATOR FUNCTION
No

CURRENT (A)
16 A

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM
Insertion

MONOBLOCK
No

NOMINAL VOLTAGE (V~)
250 V~

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
15

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American and Centralisations

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

REGULATIONS

REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | UNE 20315-1-1:2017 | IEC 60884-1 Ed 3.2 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053252093

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.054

PRODUCT NET WEIGHT
0.054

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053051504

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
53

PACKAGING WIDTH
105

PACKAGING LENGTH
221

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1229865

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.54

PACKAGING NET WEIGHT
0.54

PACKAGING WEIGHT UNIT
KGM