

POINT spotlight basic Rail 2700 K Flood White

REF. 92001022-200



BASIC INFORMATION

BODY MATERIAL

Die-cast aluminium

PACKAGING CONTENTS

1 Unit

ETIM CLASS

EC001744

APPLICATION

Domestic,Office,Retail,Contract

PACKAGING DIMENSIONS (MM)

160x255x234 mm

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DIRECTIONAL

Yes

LUMENS (LM)

1500 lm

IP RATING

IP20

DRIVER INCLUDED

Yes

NUMBER OF LUMINAIRES

1

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

ELECTRICAL CLASS

III

MACADAM STEPS

<3 Step MacAdam

POWER SUPPLY (V~)

100/277 V~

ENERGY EFFICIENCY

A+

OPTICS

Flood 30°

RAL

9016

L70 (°C)

100000h at 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Class II

COLOR TEMPERATURE (K)

2700 K

L90 (°C)

40000h at 25°C

POWER FACTOR (Φ)

> 0,98

CONTROL

On/Off

COLOR TYPE

WW

POWER (W)

25 W


CRI

90

LIGHTING EFFICIENCY (LM/W)

88 lm/W

PHOTOMETRY ASSETS – POLAR



INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Flush-mounted

INSTALLATION TYPE

Rail

REGULATIONS

EAC MARKED

Yes

ECORRAE MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8436547041220

PACKAGING VOLUME

10014720

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

234

PACKAGING GROSS WEIGHT

1.12

UNITARY PACKAGING GROSS WEIGHT

2.38

PACKAGING WIDTH

255

PACKAGING NET WEIGHT

1.02

PRODUCT NET WEIGHT

1.02

PACKAGING LENGTH

160

PACKAGING WEIGHT UNIT

KGM