Fastening bracket for Teleblock telescopic profiles with manual elevation Simon K45

REF. **KTLA4**



BASIC INFORMATION

DESCRIPTION

With black finishes and measures 108x101 mm, the fastening bracket for Teleblock telescopic profiles with manual elevation part of the series Simon K45. This piece is manufactured with thermoplastic materials and self-extinguishing, halogen-free to guarantee no flame spread in case of fire, and low toxicity of smoke. Therefore, this piece is operating normally at temperatures between -5 and 60 ° C, being able to withstand even more than those 60 ° C All this proves to the series Simon K45 has become one of the favourite series for the most demanding customers. And is that our constant effort due to innovate and always offer the best quality and guarantee have allowed our company to consolidate itself as a brand leader in the sector.

FINISH

Black

MATERIAL

Plastic

COMPATIBILITY

Teleblock with manual elevation from the Simon K45 range.

PACKAGING CONTENTS

Fastening bracket for telescopic profiles with manual elevation and installation manual.

ETIM CLASS

EC002649

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 MOhm at 500 V

IP RATING
IP4X

KIT AVAILABILITY
No

LINKABLE
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

RAL
7021

RECESS DIMENSION (MM)
Ø 114 mm

INSTALLATION AND MAINTENANCE

EXTINGUISHING (°C)
+850 °C (according to standard IEC 60670)

TYPE OF FASTENING
By tightening the fastening thread supplied with the Simon K45 Teleblock telescopic profile. Note: this article is a replacement part and is supplied with the Simon K45 Teleblock telescopic profile.

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436051676

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
3217500

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.255

PRODUCT NET WEIGHT
0.255

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436051676

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
165

PACKAGING WIDTH
130

PACKAGING LENGTH
150

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3217500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.261

PACKAGING NET WEIGHT
0.255

PACKAGING WEIGHT UNIT
KGM