Individual wall fastening bracket for Ofiblock Compact aluminium profiles Simon K45

REF. **KSF4**



BASIC INFORMATION

DESCRIPTION

Individual fastening bracket wall for Ofiblock Compact aluminium profiles, series Simon K45. This bracket has dimensions of 50 x 34 x 3 mm and requires 2 units for a correct fastening. It is made of metal and galvanised steel, complying with the UNE -s 60.670-23 European regulation. It can be position, place in rooms with a temperature of between -5 to 60 ° C, although it ' s true that is able to withstand extreme temperatures. If you want to clean this bracket to perfection, you will only need to clean it with a soft and dry cloth, never you behavior is desired to use abrasive cloths and / or abrasive cleaners containing chlorine in its formula. The range K45 SImon, in addition to socket-outlets, has floor boxes, Teleblock, wall-mounted boxes, watertight floor boxes, IP55, mini-columns, columns and ofiblock (Plus, Compact and Line) so that it can use it in the different electrical installations in your home.

FINISH

Galvinised steel

MATERIAL

Metal

COMPATIBILITY

Simon K45 Ofiblock Compact and Ofiblock Line aluminium profile

PACKAGING CONTENTS

Individual wall fastening bracket.

ETIM CLASS

EC002649

REMARKS

Requires 2 units for correct fastening.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

HEAT RESISTANCE (°C)

+125°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

IP RATING

IP4X

KIT AVAILABILITY

No

LINKABLE

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

INSTALLATION AND MAINTENANCE

EXTINGUISHING (ºC)

+850 ºC (according to standard IEC 60670)

TYPE OF FASTENING

Through the fastening of the bracket using screws and subsequent linking through the rear DIN rail on the Ofiblock profile.

SCREWS REQUIRED FOR SLAB FIXING

2 (1 for each side)

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
54432

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.015

PRODUCT NET WEIGHT
0.015

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436040199

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
72

PACKAGING WIDTH
72

PACKAGING LENGTH
105

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
544320

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.15

PACKAGING NET WEIGHT
0.15

PACKAGING WEIGHT UNIT
KGM