

2-Way push-button switch with key 5A 250V~ (key removable in rest position) and welding terminal connection system ivory Simon 31

REF. 31520-31



BASIC INFORMATION

DESCRIPTION

Protect its electrical mechanisms of unwanted tampering with the 2-way switch / push-button switch with key (with removal in standby position) of the collection Simon 31. With finishes in ivory and system solder terminal connection, it fits fully into the space, providing a simple and stylish style that adapts to any ambience decorative. With a size of 64 x 65 mm, supports a wire cross-section of 0.5 mm and is compatible with power supplies with a voltage of 250 Volts and 5 Ampere current and consists of 2 modules with capacity for 1 element. It is made of metal components with halogen-free insulation and thermoplastic trim, which protects the room in case of fire and prevents the flame spread and toxicity by smoke. It can reach a temperature range of 5 to 40 ° C and maximum temperatures of -25 to 50 ° C.

FINISH

Ivory

PACKAGING CONTENTS

Mechanism with rocker

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC001590

REMARKS

Mechanism with 2 positions and removable key in rest position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

0,5 mm

KEY-REMOVAL POSITION

Standby

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Key

VOLTAGE (V~)

250 V~

CURRENT (A)

5 A

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Welding

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 61058:2002 + EN 61058:2002 A2:2008 + EN 61058-2-1:2011

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.12

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

419050

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053007198

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

419050

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.12

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

58

PACKAGING NET WEIGHT

0.12

UNITARY PACKAGING GROSS

WEIGHT

0.12

PACKAGING WIDTH

85

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

85