

IP66 mechanism holder unit with safety lock and a British brass socket base Simon K45

REF. KSE4/23/71



BASIC INFORMATION

FINISH

Brass

MATERIAL

Metal

ETIM CLASS

EC000024

TECHNICAL INFORMATION

FORMAT

French

IP RATING

IP66

MAXIMUM LOAD (KG)

1000kg

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

KIT AVAILABILITY

No

RECESS DIMENSION (MM)

145 x 145 mm en falso suelo

INDICATOR FUNCTION

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VOLTAGE (V~)

250 V~

CURRENT (A)

16 A

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

CAN BE INSTALLED IN TRAY

Plástica

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053297797

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053297797

PACKAGING VOLUME

1664000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

65

PACKAGING GROSS WEIGHT

0.404

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

160

PACKAGING NET WEIGHT

0.354

UNITARY PACKAGING GROSS
WEIGHT

0.354

PACKAGING LENGTH

160

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.354