

Downlight 706.21 Flush mount WW Flood 1-10V Aluminium

REF. 70621133-383



BASIC INFORMATION

APPLICATION

Ambient lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY (HZ)

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS/W

900 lm/15W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

OPTICS

Flood

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

No

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

POWER (W)

15 W

COLOR TEMPERATURE (K)

3100 K

COLOR TYPE

WW

POWER SUPPLY DIMENSIONS (MM)

45x141x26 mm

CONTROL

1-10 V

LIGHTING EFFICIENCY (LM/W)

60 lm/W

SERVICE LIFE

30.000 h

CRI

80

LUMENS (LM)

900 lm

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

180

INSTALLATION TYPE

Flush mount

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING GROSS WEIGHT

0.506

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING LENGTH

0

PRODUCT NET WEIGHT

0.506

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053122211

PACKAGING GROSS WEIGHT

0.506

PACKAGING HEIGHT

135

PACKAGING LENGTH

155

PACKAGING NET WEIGHT

0.506

UNITS CONTAINED PACKAGING

1

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3.034

PACKAGING VOLUME UNIT

DMQ

PACKAGING WEIGHT UNIT

KGM

PACKAGING WIDTH

145