

Flat voice and data plate with dust cover for 1 element with 2 category 5e UTP RJ45 aluminium Simon 500 Cima

REF. 50004089-033



BASIC INFORMATION

DESCRIPTION

This flat base plate of voice and data of 1 element is designed to fit 2 connectors RJ45 category 5e UTP. It is in aluminium colour and includes a dust shutter for a better conservation of the piece, it has dimensions of 50x50x32,5 mm and consists of metal elements with in self-extinguishing, halogen-free thermoplastic insulation. This material guarantees maximum security in case of fire, as it avoids the no-propagation of the flame and guarantees the minimum toxicity if there is smoke emission. The plate has clips designed for its bond in vertical and horizontal enclosures without the need for adapter, maintenance is very important. To do this, the manufacturer advises to give a soft pass with a soft, dry cloth and do not use abrasive cleaners. The article is part of the Simon 500 Cima series, a collection designed to enhance the workplace solutions in the different environments.

FINISH

Aluminium

PACKAGING CONTENTS

Flat voice and data plate with dust cover, 2 category 5e UTP RJ45 and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

CONNECTOR CHARACTERISTICS

Category 5e UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

VERSION

Single

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097946

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.035

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

0.7

PRODUCT NET WEIGHT

0.035

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

