

MD-20 300° PIR+LUX wall surface On/Off white IP54

REF. 89202135-430



BASIC INFORMATION

DESCRIPTION

Wall-mounted PIR motion and light detector. The recommended installation height is 2 m, with a maximum height of 5 m. It has a detection angle of 300° and an opening angle of 180°. The tangential detection range is 20 m and the radial detection range is 4 m. The luminosity regulation range is 2 - 2000 lux and the timing range is 5 s - 15 min. The configuration of the detector is done via potentiometers and remote control. It has a TEACH operating mode. The control output is On/Off and the maximum switchable power is 2000 W (600 W LED). The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50°C. White finish, IP 54 protection rating, and dimensions: 114 x 74 x 128 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9010

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053341681

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.377

PRODUCT NET WEIGHT

0.252

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053341681

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

100

PACKAGING LENGTH

140

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2240000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.377

PACKAGING NET WEIGHT

0.252

PACKAGING WEIGHT UNIT

KGM