

Double German socket outlet pre-wired monoblock IP55 16A 250V~ with safety device and quick term. conn. System grey Simon 44 Aqua

REF. 4490433-035



BASIC INFORMATION

DESCRIPTION

Covers and rockers in different colours, in grey, in aluminium, in pistachio green or in a stylish red. All kinds of colors that adapt to different environments and ideal for all types of structures, in particular outdoor areas (swimming pools, washrooms, industrial, sports facilities, terraces of all kinds, gardens, lofts ...) AND is that the products of the series Simon 44 Aqua are specially designed for areas with risk permanent contact with the water or dust. If you are looking for a socket outlet for outdoor areas, you may want to this socket outlet in Schuko format and pre-wired monoblock double version (IP55 16 Amps and 250 Volt voltage) includes a safety device for the protection of the smallest of the house and quick terminal connection, being its installation really simple and very easy. The finish, this time, is grey, so if you are looking for a design that does not stand out too much on the surface-mounted on the wall, this may be a good option. Simon proves, with this collection, which has solutions for all types of problems.

FINISH

Grey

PACKAGING CONTENTS

Socket outlet, base and frame
with cover

ETIM CLASS

EC000125

COMPATIBILITY

Simon 27 mechanisms

TECHNICAL INFORMATION

AVAILABLE MARKET CE	CURRENT (A) 16 A	NOMINAL VOLTAGE (V~) 250 V~
CABLE SECTION ADMITTED (MM) 2,5 mm	IP RATING IP55	OPERATING TEMPERATURE RANGE (°C) 5 - 40 °C
NUMBER OF POSSIBLE ELEMENTS 2 elements	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	RAL 7035
FORMAT Schuko	TYPE OF MECHANISM Insertion	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
IK CLASSIFICATION 07	MONOBLOCK	VERSION Single
INDICATOR FUNCTION No		

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 15	INSTALLATION DIRECTION Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Fast
	INSTALLATION TYPE Suitable for surface mounting	

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018*1 | IEC 60884-1 Ed. 3.2*2 | UNE 20315-1-1:2017*2 | UNE 20315-1-2:2017*2 | EN IEC 60670-1:2021 + A11:2021*3 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053069912

PACKAGING VOLUME
4.079

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
5

PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
86

PACKAGING GROSS WEIGHT
1.735

UNITARY PACKAGING GROSS
WEIGHT
0.347

PACKAGING WIDTH
155

PACKAGING NET WEIGHT
1.735

PRODUCT NET WEIGHT
0.347

PACKAGING LENGTH
306

PACKAGING WEIGHT UNIT
KGM