

Angled voice and data plate with dust cover for 1 element with 1 RJ45 category 6A FTP white Simon 500 Cima

REF. 50001081-030



BASIC INFORMATION

DESCRIPTION

The plate of the Simon 500 Cima series is a angled plate for voice and data with dust cover and 1 element with 1 RJ45 category 6A FTP Keystone I, II, ATT ® / Avaya ®. Its colour white plate makes it a perfect for any type of room and decoration, especially in the that have a temperature of between -5 to 60 ° C It has been made according to the regulation TIA 568 C. 2 and in its manufacture is required components with self-extinguishing, halogen-free thermoplastic insulation; guarantees non-propagation of the spread in case of fire and low toxicity in case of gases. For the installation of this plate does not need any type of adapter as the plate of the Simon 500 Cima range includes the clips for fastening in both vertical and horizontal enclosures. It measures 50 x 50 x 54 mm

FINISH

White

PACKAGING CONTENTS

Angled voice and data plate with dust cover, RJ45 connector category 6A FTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Angled

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6A FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097700

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.059

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.18

PRODUCT NET WEIGHT

0.059

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

