

SLIM SYSTEM modular luminaire 90° angle connector with suspension cable and DALI RH power supply 150 W Black

REF. 90094114-088



BASIC INFORMATION

BODY MATERIAL

Die-cast aluminium

PACKAGING CONTENTS

1 Unit

APPLICATION

Domestic, Office, Retail, Hotel, Contract

PACKAGING DIMENSIONS (MM)

100x105x320 mm

TECHNICAL INFORMATION

IP RATING

IP20

CONTROL

DALI

ENERGY EFFICIENCY

A+

OPERATING TEMPERATURE RANGE (°C)

0 - 40 °C

DIRECTIONAL

No

PHOTOBIOLOGICAL CLASSIFICATION

Class II

RAL

9005

DRIVER INCLUDED

Yes

POWER (W)

150 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Suspended

REGULATIONS

EAC MARKED

Yes

ECORRAE MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8436547033300

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8436547033300

PACKAGING VOLUME

3208275

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

100

PACKAGING GROSS WEIGHT

2.42

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

105

PACKAGING NET WEIGHT

2.03

UNITARY PACKAGING GROSS
WEIGHT

2.16

PACKAGING LENGTH

320

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

2.03