

IP66 Mechanism holder and manual frame with schuko and RJ45 5e UTP

REF. KFH115U/72



BASIC INFORMATION

DESCRIPTION

Simon completely renews its range of watertight floor boxes for indoor and outdoor environments. This is a manual locking mechanism frame with a Schuko outlet and a category 5e UTP RJ45 connector. In combination with its base, it enables installation in technical flooring or pavement. The product design, along with its manufacture using stainless steel, ensures a robust, solid, and secure installation as it withstands a water jet of 1 kg/cm² from any direction, achieving a protection rating of IP66 when the lid is closed. It also supports a maximum load of 1500 kg and an IK08 resistance to impact. It maintains an optimal bend radius for wiring in high-category voice and data connections. Our accessory for connecting a plug with the lid closed is available, allowing us to keep our connections active with an IP54 rating (see reference KFA1001), the possibility of leveling our box in case of an uneven substrate (see reference KFA1003), or the capability to concatenate more than one box (see reference KFA1002).

FINISH

Steel

COMPATIBILITY

K45 Solutions

MATERIAL

Polycarbonate

ETIM CLASS

EC000024

REMARKS

To complete the installation of the product, it must be combined with a tray for the IP66 waterproof floor box.

TECHNICAL INFORMATION

FORMAT

Schuko

IP RATING

IP66

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

IK CLASSIFICATION

08

KIT AVAILABILITY

Yes

CURRENT (A)

16 A

MAXIMUM LOAD (KG)

1500 Kg - Closed box | 250 Kg - Open box

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

REMOVAL OF THE SOCKET

Only with tool

NUMBER OF COVER OPENING POSITIONS

1

REMOVAL OF THE FRAME

Only with tool

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 50173-1:2018 | EN 60670-23:2008 | EN IEC 63000:2018 | IEC 60884-1 Ed 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 |

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053332764

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.157

PRODUCT NET WEIGHT

0.13

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053332764

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

114

PACKAGING WIDTH

124

PACKAGING LENGTH

130

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1837680000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.157

PACKAGING NET WEIGHT

0.13

PACKAGING WEIGHT UNIT

KGM