


Flush-mount trim cover for adjustable floor box or service cover 2 elements graphite Simon 500 Cima

REF. 52053101-038



BASIC INFORMATION

DESCRIPTION

The accessories for electrical systems of the Simon 500 Cima series have aims to offer the best protection, as well as the operation more user-friendly to the same. A good example of this is the Flush-mount trim cover for adjustable floor box or service cover with 2 elements in graphite colour included in this range, its structure has been designed with halogen-free thermoplastic material that guarantees no flame propagation in case of fire and low toxicity in the event of smoke generation. Its installation can be carried out in a few minutes, so in concrete floor and raised floor through the adjustable floor boxes or inspection covers. Its dimensions are 154 x 66 x 5 mm, it also, this product includes optional element to combine with the floor box if not installing the same floor lining.

FINISH

Graphite

PACKAGING CONTENTS

Trim cover

MATERIAL

Plastic

ETIM CLASS

EC002417

REMARKS

Optional element. To combine with the floor box if not installing the same floor finish.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IK CLASSIFICATION

08

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

AVAILABLE IN

2, 4, 6, 8 and 12 elements

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

NUMBER OF MODULES

2 modules

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

IP RATING

IP4X

RAL

7021

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

KIT AVAILABILITY

No

VERSION

2 elements

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using the screws supplied

INSTALLATION TYPE

In raised or concrete floor with adjustable floor boxes or service covers

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

INSTALLATION DIRECTION

Horizontal, Vertical

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT 0	UNITARY PACKAGING WEIGHT UNIT KGM	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING WIDTH 0	PACKAGING EAN 8421053101490	PACKAGING VOLUME 1.714
UNITARY PACKAGING LENGTH 0	UNITS CONTAINED PACKAGING 10	PACKAGING VOLUME UNIT DMQ
UNITARY PACKAGING VOLUME 0	PACKAGING HEIGHT 70	PACKAGING GROSS WEIGHT 0
UNITARY PACKAGING GROSS WEIGHT 0.049	PACKAGING WIDTH 154	PACKAGING NET WEIGHT 0.49
PRODUCT NET WEIGHT 0.049	PACKAGING LENGTH 159	PACKAGING WEIGHT UNIT KGM

