

Angled voice and data plate with dust cover for 2 RJ45 connectors graphite Simon 75

REF. 75579-38



BASIC INFORMATION

DESCRIPTION

The Simon 75 series gives the plate of voice and data tilted plate with dust cover for 2 RJ45 connectors and is available in 4 different finishes, but it is always recommended to choose the frame of the same colour of the plate that we select. The plate of voice board is RJ45 format. This voice and data plate does not apply regulation. The manufacturing material of the voice and data plate is thermoplastic, with a plastic graphite finish is recommended for maintenance use a soft cloth slightly moistened in soapy water. This voice and data plate is inclined and has 2 connectors and a dust shutter but does not include an RJ45 adaptor module. This model of voice and data plate has no engraving at all. The individual version of the voice and data tilted plate with dust cover for two connectors, this model of plate of voice and data tilt plate includes one element but does not include signaling function or modules. The limit of the recommended temperature range is from 5 to 40°C reaching maximum temperatures of -25 to 50°C. It is suitable for installations in surface mounting or flush mounting.

FINISH

Graphite

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Plate

SYMBOL

Without engravings

COMPATIBILITY

Simon 75 mechanisms

ETIM CLASS

EC000018

REMARKS

Available in 4 finishes. It is recommended to choose a frame the same colour as the selected plate.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

No

PLATE TYPE

Angled

NUMBER OF CONNECTORS

2

IP RATING

IP20

RJ45 ADAPTOR MODULE

Not Included

DUST SHUTTER

Yes

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

VERSION

Single

FORMAT

RJ45

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + EN 50581:2012

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
1517738

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.054

PRODUCT NET WEIGHT
0.054

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053055410

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
82

PACKAGING WIDTH
83

PACKAGING LENGTH
223

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
3026595

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.27

PACKAGING NET WEIGHT
0.27

PACKAGING WEIGHT UNIT
KGM