# Complete kit with dual opening cover, brushes, 4xUSB charger and 6 schuko socket outlets white S400 Indesk Duo

REF. **46423000-130**



## BASIC INFORMATION

### DESCRIPTION

Avoiding the negative consequences of a fire in an electrical system is possible if we rely on the complete kit integrated into the table with two openings, brushes, 4xUSB charger, and six schuko socket bases in white from the Simon 400 Indesk Duo series. How does it achieve this? Thanks to the painted steel enclosure, anodized aluminum profile, covers, and fasteners made of halogen-free, self-extinguishing thermoplastic. Other qualities include: intensity of 16 A, voltage of 250 V~, insulation resistance of >5 MO at 500 V, Wieland® gst18i connector with three male poles aerial with a 22 cm patch cord, and dielectric strength without drilling or contouring of 2000 V at 50 Hz for one minute. To complete the installation of the product, it must be combined with the functions of Simon 400 Indesk Duo. All at the most competitive price we can find in the market.

### FINISH

White

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with brush

### DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

### FORMAT
Schuko

### HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)
>5 MΩ a 500 V

### CURRENT (A)
16 A

### IP RATING
IP30

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

### NOMINAL VOLTAGE (V~)
250 V~

### TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL
9016

### RECESS DIMENSION (MM)
228 x 175 mm (± 2mm)

### NUMBER OF SOCKETS
6 sockets for standard current circuit

### NUMBER OF USB CHARGERS
2

### VERSION
8 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS
With brush

### CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

### NUMBER OF COVER OPENING POSITIONS
2

### EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING
By lateral tightening of claws provided with the enclosure. Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

### REMOVAL OF THE FRAME
Only with tool

### INSTALLATION TYPE
Suitable for recessed mount in furniture.

### OPENING ORIENTATION
At 45° and 135°

### REMOVAL OF THE PLATE
Only with tool

### SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2014/30/UE EMC;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;EN 60950-1:2006;EN 60950-1:2006 A11:2009;EN 60950-1:2006 A1:2010;EN 60950-1:2006 A12:2011;EN 60950-1:2006 A2:2011*3;ETSI-EN 301489-34 V1.4.1;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE
8421053273661

### UNITARY PACKAGING HEIGHT
0

### UNITARY PACKAGING WIDTH
0

### UNITARY PACKAGING LENGTH
0

### UNITARY PACKAGING MEASUREMENT UNIT
MMT

### UNITARY PACKAGING VOLUME
0

### UNITARY PACKAGING VOLUME UNIT
MMQ

### UNITARY PACKAGING GROSS WEIGHT
2.35

### PRODUCT NET WEIGHT
2.35

### UNITARY PACKAGING WEIGHT UNIT
KGM

### PACKAGING EAN
8421053273661

### UNITS CONTAINED PACKAGING
1

### PACKAGING HEIGHT
130

### PACKAGING WIDTH
215

### PACKAGING LENGTH
345

### PACKAGING MEASUREMENT UNIT
MMT

### PACKAGING VOLUME
9642750

### PACKAGING VOLUME UNIT
MMQ

### PACKAGING GROSS WEIGHT
0

### PACKAGING NET WEIGHT
2.35

### PACKAGING WEIGHT UNIT
KGM