

Floodlight Protect 14,3W 3000K with detector 10m 180° PIR+LUX anthracite IP54

REF. 89193002-143



BASIC INFORMATION

DESCRIPTION

Projector with PIR detector. The power is 14.3 W, the luminous flux is 1642 lm and the color temperature is 3000 K.

The maximum installation height is 4m and the installation is on the wall (surface). The detection range is 10m and the detection angle is 180°.

The brightness adjustment range is 2 - 2000 lux and the timing range is 8 s - 35 min.

The configuration of the luminaire is done through potentiometers.

The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C.

Degree of protection IP 54 and IK 03 and dimensions: 195 x 195 x 187 mm.

3-year warranty.

For more product information visit the STEINEL website by clicking [here](#).

FINISH

Anthracite

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

IK CLASSIFICATION

03

OPERATING TEMPERATURE RANGE (°C)

-10...+40

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Wall surface mounting

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053429709

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

1.025

PRODUCT NET WEIGHT

0.63

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053429709

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

232

PACKAGING WIDTH

182

PACKAGING LENGTH

295

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.025

PACKAGING NET WEIGHT

0.63

PACKAGING WEIGHT UNIT

KGM