

Voice and data angled plate with dust cover for 1 element and 1 RJ45 connector category 5e FTP aluminium Simon K45

REF. K8095F/8



BASIC INFORMATION

DESCRIPTION

Do you want to have security in its electronic systems? Then you must be in the angled voice and data plate with dust cover for an element and an RJ45 connector with insertion tool category 5e FTP in aluminium colour of the series Simon K45, an element that guarantees no flame propagation in case of fire and the low toxicity in case of smoke thanks to the metal components with self-extinguishing and halogen-free thermoplastic insulation. with which it has been made stand out. This plate of voice and data cabling has a 22-24 AWG and measures 45 x 45 x 59 ' 4 mm You can be installed on the surface-mounted or flush mounted. Also, in case of combining the voice and data plate in vertical enclosures (mini-columns, columns, Teleblock, channels, mechanism holders) you must use the 90° positioner (reference K66) to guide the plate into a vertical position.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Voice and data tilted plate with dust cover, direct module for snap-fit connector, RJ45 category 5e FTP connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

DUST SHUTTER

Yes

NUMBER OF MODULES

Half

AVAILABLE IN

Plate with 1 RJ45 connector

FORMAT

RJ45

PLATE TYPE

Angled

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Supplied with the voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e FTP

KIT AVAILABILITY

No

RJ45 CONNECTORS

Included in voice and data plate

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.026

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2871375

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436046290

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

5893875

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.26

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

95

PACKAGING NET WEIGHT

0.26

UNITARY PACKAGING GROSS WEIGHT

0.026

PACKAGING WIDTH

155

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

195