

# Modular Luminaire Simon 720 Advance M4 120x30 BIO 1-10 V

REF. 72061140-880



## BASIC INFORMATION

### PACKAGING CONTENTS

1 unit

### ETIM CLASS

EC002892

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### DRIVER INCLUDED

Yes

### LUMENS (LM)

4000 lm

### IP RATING

IP44

### INTEGRATED POWER SUPPLY

Yes

### LUMENS/W

4000 lm/ 34 W

### OPERATING TEMPERATURE RANGE (°C)

0 to 40° C

### L70 (°C)

100.000 h at 25 °C

### OPTICS

Translucent

### POWER SUPPLY (V~)

100/240 V~

### L90 (°C)

40.000 h at 25 °C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

### COLOR TEMPERATURE (K)

2700K – 5700K

### LIGHT BEAM APERTURE ANGLE (°)

120°

### POWER (W)

34 W

### CONTROL

1-10 V

### LIGHTING EFFICIENCY (LM/W)

118 lm/w

### SERVICE LIFE

50.000 h

### CHROMATICS CRI ICONS

CRI  
82

## INSTALLATION AND MAINTENANCE

### INSTALLATION ALTERNATIVES

Surface-mounted | Plaster ceiling | Concealed profile | Semi-concealed profile

### INSTALLATION TYPE

False ceiling, visible hardware

## REGULATIONS

### WARRANTY

5 years

## LOGISTICS INFORMATION

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

5.62

### PRODUCT NET WEIGHT

5

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053091265

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

65

### PACKAGING WIDTH

300

### PACKAGING LENGTH

1200

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

23400000

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

5

### PACKAGING WEIGHT UNIT

KGM