

Single-pole push-button switch 16AX 230V~ with fast terminal connection system matt white Simon 270

REF. 20000111-190



BASIC INFORMATION

FINISH

Matt white

MATERIAL

Thermoplastic

COMPATIBILITY

Simon 270 frames

ETIM CLASS

EC001590

TECHNICAL INFORMATION

AVAILABLE MARKET CE	INDICATOR FUNCTION No	OPERATING TEMPERATURE RANGE (°C) 5 - 45 °C
CABLE SECTION ADMITTED (MM) 1.5 - 2.5	CURRENT (A) 16 AX	POWER SUPPLY (V~) 230 V~
NUMBER OF CONTACTS 2	IP RATING IP20	RAL 9003
NUMBER OF POSSIBLE ELEMENTS 1	MAINTENANCE Clean with a soft cloth and soapy water. Do not use abrasive cloths and/or cleaners containing chlorine.	RECESS DIMENSION (MM) 40
FORMAT Push-button	NOMINAL VOLTAGE (V~) 230 V~	VOLTAGE (V~) 127/230 V~
FREQUENCY 50 - 60 Hz		NUMBER OF WIRES 2

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 15	REMOVAL OF COVER Only with tool	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Screw
CLAW Simon 27	INSTALLATION DIRECTION Horizontal, Vertical	

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053315767

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.032

PRODUCT NET WEIGHT

0.032

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053315378

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

47.75

PACKAGING WIDTH

57

PACKAGING LENGTH

262

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

713098.5

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.32

PACKAGING WEIGHT UNIT

KGM

