Adjustable depth box for 4 modules S to be installed in concrete graphite color Simon CIMA

REF. **SF470/14**



BASIC INFORMATION

FINISH
Graphite

MATERIAL
Various

COMPATIBILITY
With Simon Series S and Simon 25 / Simon K45 (via adapter) mechanisms.

ETIM CLASS
EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES
12

HEAT RESISTANCE (°C)
+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION
08

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)
1300kg

RAL
7021

RECESS DIMENSION (MM)
170 x 265 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

NUMBER OF COVER OPENING POSITIONS
2

REMOVAL OF COVER
Only with tool

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME
Only with tool

CAN BE INSTALLED IN TRAY
Plástica y metálica

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436052796

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
4982940

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
1.615

PRODUCT NET WEIGHT
1.615

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436052796

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
95

PACKAGING WIDTH
186

PACKAGING LENGTH
282

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
4982940

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.85

PACKAGING NET WEIGHT
1.615

PACKAGING WEIGHT UNIT
KGM