2-way rotary dimmer switch for half element 40 to 500W/VA white Simon 27 Play

REF. **27313-34**



BASIC INFORMATION

DESCRIPTION

Each activity requires a specific light intensity. The excess or lack of lighting can cause problems when carrying out different tasks in our home or work. - thanks to this regulator 2-way switch half element rotary light from 40 to 500 W / VA of the Simon 27 Play series, this will never be a problem. Its value for money is unrivalled in the market regulator. This is a universal electronic narrow-module voltage available in white colour. Its ease of use, with a rotary type of operation, is another of its advantages, besides being suitable for surface and flush mounting. For its maintenance, it is only necessary to a soft cloth slightly moistened in soapy water, like the rest of our products, the quality of their materials is excellent with electronic components with halogen-free insulation and thermoplastic trim.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

COMPATIBLE WITH MECHANICAL 2-WAY/CROSSOVER SWITCH

Yes

COMPATIBLE WITH 230V INCANDESCENT AND HALOGEN LAMPS (W)

500 VA

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

COMPATIBLE WITH MECHANICAL SWITCH

No

PACKAGING CONTENTS

Dimmer and instruction sheet

ETIM CLASS

EC000025

REMARKS

Two main electronic voltage regulators cannot be connected in the same circuit.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 1,5 to 2,5 mm

NUMBER OF CONTACTS
3

NUMBER OF CONTROLLABLE CIRCUITS
1

COMPATIBLE WITH HALOGENS WITH ELECTROMAGNETIC TRANSFORMER (W)
500 VA

COMPATIBLE WITH ELECTRONIC AUXILIARY
No

NUMBER OF POSSIBLE ELEMENTS
Half element

COMPATIBLE WITH FLUORESCENT LAMPS WITH 1-10V DIMMABLE ELECTRONIC BALLAST
No

COMPATIBLE WITH FLUORESCENT LAMPS (VA)
No

INDICATOR FUNCTION
Yes

IP RATING
IP20

COMPATIBLE WITH LOW CONSUMPTION (W)
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM POWER (W)
500

MAXIMUM QUANTITY PER CIRCUIT
1

TYPE OF MECHANISM
Rotary

MINIMUM POWER (W)
40

COMPATIBLE WITH MOTORS (VA)
No

OPERATING TEMPERATURE RANGE (°C)
0 - 40 °C

POWER SUPPLY (V~)
230 V~

TYPE
2-way dimmer switch

VERSION
Single

NUMBER OF WIRES
2

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
8

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American and Centralisations

INSTALLATION TYPE
Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD|Dir. 2014/30/UE EMC|Dir. 2011/65/UE RoHS + post. mod.|EN 60669-2-1:2004|EN 60669-2-1:2004 A1:2009|EN 60669-2-1:2004 A12:2010|EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053060148

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.02

PRODUCT NET WEIGHT
0.02

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053060148

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
23

PACKAGING WIDTH
57

PACKAGING LENGTH
84

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
110.124

PACKAGING VOLUME UNIT
CMQ

PACKAGING GROSS WEIGHT
0.05

PACKAGING NET WEIGHT
0.02

PACKAGING WEIGHT UNIT
KGM