

Back kit for 1 2P+E socket with integrated 2.1A USB charger with smartcharge Simon 100

REF. 10010126-039



BASIC INFORMATION

FINISH

Black

PACKAGING CONTENTS

Mechanism and instructions

ETIM CLASS

EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

TYPE OF MECHANISM

Insertion

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

universal

INSTALLATION DIRECTION

Horizontal and vertical

INSTALLATION TYPE

Suitable for flush mounting

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2011 IEC 60884-1 Ed. 3.2 ETSI-EN 301489-34 V1.4.1 EN 50581:2012

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053232002

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.163

PRODUCT NET WEIGHT

0.163

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053232002

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

76

PACKAGING WIDTH

90

PACKAGING LENGTH

88

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

601920

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.163

PACKAGING WEIGHT UNIT

KGM