

DualTech presence and brightness detector 10m DALI-2 Input white

REF. 89252323-230



BASIC INFORMATION

DESCRIPTION

Presence and brightness detector for flush-mounted PIR + US. The recommended installation height is 2.8 m, with a maximum height of 3.5 m. It has a detection angle of 360° and an opening angle of 180°. The tangential detection range is 10 m and the radial detection range is 10 m.

The brightness regulation range is 10 - 1000 lux and the timing range is 30 s - 30 min. The configuration of the detector is done via DALI.

It features TEACH operating mode. Possibility of interconnection between sensors via DALI. The control protocol is DALI-2 Input. The typical consumption is 16 mA.

The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: -25 - 55 °C.

White finish, IP 20 protection rating and dimensions: 120 x 120 x 66 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9010

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053381946

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.255

PRODUCT NET WEIGHT

0.145

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053381946

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

100

PACKAGING WIDTH

160

PACKAGING LENGTH

142

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.255

PACKAGING NET WEIGHT

0.145

PACKAGING WEIGHT UNIT

KGM