# Spotlight 615 rail 3000 K Flood white DALI

REF. **61500330-383**

## BASIC INFORMATION

**FINISH**
White

**APPLICATION**
Accent lighting

**ETIM CLASS**
EC001744

**MATERIAL**
Aluminium

**PACKAGING CONTENTS**
1 unit

## TECHNICAL INFORMATION

**FREQUENCY**
50 - 60 Hz

**IP RATING**
IP20

**OPERATING TEMPERATURE RANGE (°C)**
35 °C maximum

**POWER SUPPLY (V~)**
220/240 V~

**COLOR TEMPERATURE (K)**
3000 K

**CONTROL**
DALI2

**CRI**
90

**DIRECTIONAL**
Yes

**DRIVER INCLUDED**
Yes

**L70 (°C)**
100,000 h at 25 °C

**L90 (°C)**
50,000 h at 25 °C

**COLOR TYPE**
WW

**LIGHTING EFFICIENCY (LM/W)**
80 lm/W

**LUMENS (LM)**
2000 lm

**LUMENS/W**
2000lm/ 25W

**OPTICS**
Flood

**PHOTOBIOLOGICAL CLASSIFICATION**
Exempt category

**POWER (W)**
25 W

**CHROMATICS CRI ICONS**

## INSTALLATION AND MAINTENANCE

**INSTALLATION TYPE**
3-phase adjustable rail

## REGULATIONS

**WARRANTY**
5 years

## LOGISTICS INFORMATION

UNITARY EAN CODE
8421053207185

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.846

PRODUCT NET WEIGHT
0.635

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053207185

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
84

PACKAGING WIDTH
177

PACKAGING LENGTH
296

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
4400928

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.846

PACKAGING NET WEIGHT
0.635

PACKAGING WEIGHT UNIT
KGM